

**Model No .**                      **ABDJ183317**

**Electrical specifications**

<b>Frequency range</b>	<b>1710-1850 MHz</b>
<b>Gain</b>	<b>17dBi</b>
<b>VSWR/50 Ohms</b>	<b>&lt; 1.5</b>
<b>Horizontal beamwidth</b>	<b>33°</b>
<b>Vertical beamwidth</b>	<b>13°</b>
<b>Polarization</b>	<b>Vertical</b>
<b>Maximum input power</b>	<b>100W</b>
<b>Electrical downtilt</b>	<b>0°</b>
<b>Front-to-back ratio</b>	<b>&gt; 23dB</b>
<b>Connector</b>	<b>N-Female</b>
<b>IM.3rd order(2×43dBm)</b>	<b>&lt; -107 dBm</b>
<b>Lightning protection</b>	<b>Direct ground</b>



**Mechanical specifications**

<b>Dimensions of antenna(L×W×H)</b>	<b>800mm ×454 mm ×210mm</b>
<b>Weight of antenna</b>	<b>0.6 Kg</b>
<b>Weight of mounting kits</b>	<b>1.5 Kg</b>
<b>Installation position adjustment</b>	
<b>Horizontal</b>	<b>360°</b>
<b>Angle of pitch</b>	<b>0~15°</b>
<b>Diameter of installation pole</b>	<b>60~110 mm</b>
<b>Radome material</b>	<b>Fiberglass</b>
<b>Rated wind speed</b>	<b>200 Km/h</b>